

# Waterflex® WF-2—Wafer Style Check Valve

## Features & Benefits

- High Backpressure Rating
- Seals Drop-Tight Eliminating Backflow
- No Springs or Packing Seals
- Light Weight
- Non-slamming
- Low Profile, Short Face to Face

## Materials of Construction

- Disc: Carbon Steel, Stainless Steel, PVC (low pressure only)
- Waterflex® Membrane: PGR, Neoprene, Buna-N, Hypalon® and NSF-61-Approved EPDM



Patent No. 76412514

The wafer-style Series WF-2 is an entirely new check valve design specifically engineered for water applications. The all-new WF-2 provides very low headloss characteristics, with high backpressure ratings comparable to other valve styles such as lever and weight or spring-loaded disks.

The WF-2 operates solely on line pressure and back pressure to open and close...no outside energy source is required. As line pressure builds, the 100% elastomeric disc is folded away from the perforated plate, allowing water to pass. The "memory" of the rubber will cause the disk to return flat, and back-pressure will seal the disk against the plate to prevent backflow. The WF-2 is designed to be inserted between two mating flanges. Its face-to-face dimension is the smallest available for any check valve.

The Elastomer Waterflex® is more cost effective than other valve styles. Moving parts such as hinges and springs can seize if routine maintenance and lubrication is not performed. The WF-2 has no moving parts that require maintenance or repairs, so operational costs are low and service life is long.

Nominal Pipe Size	Outside Diameter	Pressure rating ANSI lbs
4"	6.19"	150
6"	8.50"	150
8"	10.63"	125
10"	12.75"	100
12"	15"	75
16"	18.5"	75
24"	27.25"	50
30"	34.5"	50
36"	41"	50
42"	47.75"	50
48"	54.25"	50

Consult factory for higher working pressure.

## Headloss vs. Pipe Velocity

